



Inter-Drain 2028T

## AGRICULTURE DRAINAGE MACHINE

NEW CABIN



TIER 4 ENGINE



Inter-Drain 1824T



Inter-Drain 4045T

## T-TRENCHERS



# Inter-Drain



TRENCHER TYPE	1824T	2028T	3035T	4045T
<b>ENGINE</b>				
Make 1)	Volvo	Volvo	Volvo	Volvo
Engine power Hp. (kw)	265 (195)	305 (225)	350 (257)	422 (310)
Fuel tank capacity	350 Liter	475 Liter	650 Liter	650 Liter
Electrical system	24 Volt DC	24 Volt DC	24 Volt DC	24 Volt DC
<b>TRACKS</b>				
Propulsion	Independent	Independent	Independent	Independent
Transmission	Hydrost.	Hydrost.	Hydrost.	Hydrost.
Suspension	Oscill.	Oscill.	Oscill.	Oscill.
Type (equiv. cater.)	D4	D4	D4	D5B
Length 2)	4,50 m.	4,80 m.	5,60 m.	5,80 m.
Width 2)	0,60 m.	0,60 m.	0,70 m.	0,70 m.
<b>DIGGING UNIT</b>				
Max. speed	6 m/sec	6 m/sec.	6,5 m/sec.	6 m/sec.
Chaindrive	Mech.	Mech.	Mech.	Mech.
Digging angle	60°	60°	60°	60°
Swivel	6°	6°	6°	6°
Tilt control	Automat.	Automat.	Automat.	Automat.
Pipe shute	Independent	Independent	Independent	Independent
Float control	Press. var.	Press. var.	Press. var.	Press. var.
<b>PERFORMANCE</b>				
Working speed	0-3,6 km/h	0-3,6 km/h	0-3,6 km/h	0-3,6 km/h
Travel speed	4,5 km/h	5,5 km/h	5,5 km/h	5,5 km/h
Digging depth (standard)	1,80 m.	2,10 m.	2,10 m.	2,40 m.
Digging depth 3) (max.)	2,10 m.	2,40 m.	3,00 m.	6,00 m.
Digging width 3) (min.)	0,13 m.	0,13 m.	0,20 m.	0,20 m.
Digging width 3) (max.)	0,50 m.	0,50 m.	0,60 m.	0,60 m.
<b>SIZES AND WEIGHT</b>				
Length	10 m.	10,30 m.	11,50 m.	11,50 m.
Width	2,65 m.	2,70 m.	2,95 m.	2,95 m.
Height (transp. pos.)	2,95 m.	2,95 m.	3,10 m.	3,10 m.
Weight (approx)	16 t.	18 t.	22 t.	25t.
<b>OPTIONS*</b>				
1) Other engine make				
2) Longer, wider tracks	1 meter =3,28 feet			
3) Different trench sizes	1 ton = 2200 lbs			
Auto grade system				
Different cab. position				
Slope compensation				
Automatic transmission.				
Spoil eject. by conv. belt				