



Inter-Drain 2050TL

AGRICULTURE DRAINAGE MACHINE

NEW CABIN



TIER 4 ENGINE



Inter-Drain 2040TL



Inter-Drain 2050TL

TL-PLOWS



PLOUGH TYPE	2030TL	2040TL	2050TL
ENGINE			
Make 1)	Volvo	Volvo	Volvo
Power Hp. (kw)	350 (257)	422 (310)	540(371)
Fuel tank capacity	850 L.	1000 L.	1000 L.
Electrical system	24 Volt	24 Volt	24 Volt
TRACKS			
Propulsion	Independent	Independent	Independent
Transmission	Hydrost.	Hydrost.	Hydrost.
Suspension	Oscill.	Oscill.	Oscill.
Type (equiv. cater)	D5B	D5B/D7	D7G
Length 2)	6 m.	6 m.	6 m.
Width 2)	0,76 m. (2' 4")	0,80 m.	0,80 m.
Ground pressure	0,33 kg/cm ²	0,37 kg/cm ²	0,40 kg/cm ²
PLOUGH			
Depth regulating system	Single parall.	Single parall.	Single parall.
Type	I-V	I-V	I-V
Swivel	6°	6°	6°
Tilt control	Automat.	Automat.	Automat.
Float control	Press. Var	Press. Var	Press. var.
PERFORMANCE			
Working speed	0-3 km/h	0-3,2 km/h	0-3,5 km/h
Travel speed	5 km/h	5,5 km/h	5,5 km/h
Depth (average)	1,00-1,50 m.	1,20-1,60 m.	1,20-1,80 m.
Depth (max.)*	1,80 m.	2,00 m.	2,00 m.
Pipe sizes up till*	Ø 0,20 m.	Ø 0,20 m.	Ø 0,20 m.
Theor. drawbar pull (approx.)	30 t.	37 t.	37 t.
SIZES AND WEIGHT			
Length	9,6 m.	10 m.	10 m.
Width	2,95 m.	3,2 m.	3,2 m.
Height (transp. Pos.)	3,1 m.	3,25 m.	3,25 m.
Weight (approx)	28 t.	32 t.	34 t.
OPTIONS			
1) Other engine make			
2) Longer, wider tracks			
Auto grade system			
Multi. plough			
V-shape plough			
Company colours			

1 m. = 3,28 feet
1 ton = 2200 lbs